

2026-06-24

PRODUCT CERTIFICATE



Product	Bale Strap 215kgf 500m WG20
Code	WG2050
Unit	pcs
Weight (g)	1594.0
Dimensions (cm)	Ø14.0, h 14.0
Bale (kg)	50
Box size (l*w*h cm)	28*28*28
Boxes / layer europallet	8
Breaking Strength (kgf, min.)	215
CPV	39561120-9
Coils/EUR1 pallet (pcs)	384
Coils/box (pcs)	8
HS8	39239000
Length (m, ±3%) *	500
Tube id (mm)	63
Width (mm, ±10%) *	7

Description

Lampero Bale Strap WG20 is a non-woven, textile polyester strap also known as hotmelt strap or PES strap.

Lampero Bale Strap offers impressive weathering and chemical resistance, along with 13% elasticity. This allows it to secure goods with exceptional strength while absorbing thermal expansion, contraction, and mechanical shocks.

Lampero Bale Strap WG20 is ideal for binding light bales of cardboard max. 70 kg and foil max. 50 kg, usually made using 3-4 ton vertical balers. Bales are usually bound by hand. For added convenience, the H22 Tensioner and CB4F buckles can be used for retensioning. WG20 Bale strap is suitable for use with the following balers: Bramidan B3/B4, Orwak 3100/Compact 3110/5070, Strautmann BalePress 3/BalePress 4, HSM V-Press 503/V-Press 504, Mil-Tek 102, Macfab 40, Austropressen K65/K70, LSM V5, RTV 4.

The strap is made of virgin polyester yarn and adhesive. It complies with EU safety standards for packaging of foodstuffs and personal care products according to Regulation (EC) No 1935/2004.

The product is not subject to REACH registration and contains no SVHC-listed substances (ECHA, 2018-06-28). It is free from heavy metals (Pb, Cd, Hg and Cr(VI)), PFAS, and Persistent Organic Pollutants (POPs). The strap is not recyclable.

*Product dimensions marked with an asterisk may vary within the specified tolerance.

